

Technical Data Sheet

www.pamfast.com

PAMFAST ADHESIVES

UX8012

* The last digit in the product's item number indicates its form:

1=1¾" plug 2= ½" stick

DESCRIPTION:

This hot melt adhesive is one of the most unique products in the PAM product line and performs similar to a permanent pressure sensitive hot melt adhesive. It bonds to a variety of metals, concrete, carpet tack strips, Hardie board, plastics, PVC, EPDM rubber, foils, wood, and other unique substrates. It is clear in color that has a medium open and set time.

PRODUCT SPECIFICATIONS:

SOFTENING POINT (F)	194
VISCOSITY AT 356 (F)	4,000
HEAT RESISTANCE (F)	160
COLD RESISTANCE (F)	5
WPS 68 Heat Resistance@130F	100g/cm ² (shear load)
OPEN TIME	50 SECONDS
SET TIME	60 SECONDS
WORKING TEMPERATURE (F)	356-392

APPLICATION:

For best results use in PAM HB 220 Glue Stick Guns.

AVAILABLE FORMS:

½" X 10" sticks in 22 pound cartons

FDA STATUS:

FDA lists product ingredients under CFR 175.105, Adhesives.

UPDATED in January 2009

Important Notice: The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

Warning: The molten adhesive and nozzle of the various tools can reach temperatures of up to 400°F. and could cause skin burns if used carelessly. Use appropriate protective gear when working with this material. Always use in well-ventilated area.

The logo for PAM, consisting of the letters "PAM" in a bold, white, sans-serif font, set against a solid orange rectangular background.

PAM Fastening Technology, Inc.

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com